

LITHIUM BATTERY CR14335

优点及特征

工作电压平稳, 在应用的寿命期内具有高而稳定的电压响应 低自放电率 (在 +25°C 的条件下贮存, 年自放电率低于 2%)
气密的玻璃封口金属外盖
卷绕式结构
已通过 CE、SGS 认证
通过 ISO9001 质量管理体系认证

Key Characteristics

High and stable operating voltage
Low self-discharge rate (less than 2% after 1 year storage at +25°C)
Hermetic glass-to-metal sealing
Spiral type
CE, SGS recognized
ISO9001 approved

性能数据


标称容量 800mAh
额定电压 3.0V
最大连续工作电流 1000mA
最大脉冲电流 2000mA
电池重量 约13g
电池最大外形尺寸 $\varnothing 14.5 \times 33.5$ mm
工作温度 $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

Electrical Characteristics

Nominal capacity 800mAh
Nominal voltage 3.0V
Max. continuous current 1000mA
Max. pulse current capability 2000mA
Weight Approx. 13g
Dimension $\varnothing 14.5 \times 33.5$ mm
Operating temperature range $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$


常温负载特性

Discharge Characteristics




容量\电流\温度关系特性

Load-Capacity Characteristics




脉冲放电特性 2

Pulse Discharge Characteristics 2



电池尺寸图

Battery Dimension



- + Available terminations:
-P axial pins
-2PT/T radial pins
-3PT/4PT polarized tabs

极端样式:

- P 轴向碰焊线
- 2PT/T 径向插件
- 3PT/4PT 多脚插件

- + Available terminations can be made as requested.
特殊极端样式可按客户要求订做